

Mercedes 722.7

Page 2: Oil Level Instructions.

Page 3: Clutch Clearance Specifications.

Automatic Choice



Automatic Choice Ltd.
Unit 1A Farrington Fields
Farrington Gurney
Bristol
BS39 6UU
United Kingdom
Telephone: +44 (0)1761 452255
Fax: +44 (0)1761 453049
e-mail: info@automaticchoice.com

Automatic Choice Europe B.V.
De Schutterij 19
3905 PJ V eenendaal
The Netherlands
Telephone: +31 (0)318 590 591
Fax: +31 (0)318 590 177
e-mail: ace@automaticchoice.com

Automatic Choice S.L.
C/Moscatel 11
Pol. Ind. Arroyo De La Miel
Benalmádena
29631 Málaga
España
Telephone: +34 902 503 277
Fax: +34 952 440 798
e-mail: acexxi@acexxi.com

Automatic Choice EOOD
23, Nikolay Haytov Street
Floor 1 Office 4
1172 Sofia
Bulgaria
Telephone: +359 2 969 8609
Fax: +359 2 963 4565
e-mail: stelliana@automaticchoice.com

TECHNICAL INFORMATION BULLETIN

722.7 Checking Oil Level

Instructions:

To set the correct fluid level a special dipstick is required AC Part No. M168.DIP01, the dipstick is marked with the numerals 1 – 12 and the correct level is set between 8 – 10 with the fluid at working temperature.



TECHNICAL INFORMATION BULLETIN

Mercedes 722-700 Clutch Clearances

<i>Clutch Pack</i>	<i>Clearance</i>
'K1' & 'K2'	0.50mm – 0.70mm
'K3' & 'K4'	0.50mm – 0.90mm
'K5'	1.00mm – 1.40mm
'KR'	1.00mm – 1.20mm

The adjustment is made by altering the thickness of the retaining circlip.